



Amadeus 7800L

Specifications

Processor	Supports Intel® Pentium 4 / Celeron D processors in LGA775 package Supports Intel Hyper-Threading Technology Supports FSB 533/800MHz
Cache L2 Memory	1MB L2 cache, depends on Processor
Chipset	VIA® P4M800 Chipset
Audio	Integrated AC'97 codec supported 6 channels software audio codec Realtek ALC655
Video	Integrated S3 UniChrome™ Graphics Share Memory up to 64MB
System Memory	Supports two DDR memory modules, up to 2GB Supports DDR 400 memory interface
On-Board IDE	Supports 2 Ultra ATA-100 ports Supports 2 Serial ATA-150 ports
Standard Diskette Size	3.25"/1.44MB FDD
Optical Drive	52x CD-ROM Drive CD-RW Drive (optional)
Network Interface	Integrated Realtek® 8201CL 10/100 LAN
Modem	56kbps V.92 Internal PCI Fax/Modem (optional)
Expansion Slots	One AGP 8X Two 32-bit PCI
Drive Bays	Two 5.25" for CD-ROM Drive One 3.5" for FDD Two 3.5" (hidden) for HDD
I/O Interface	1 PS/2 keyboard & mouse 1 parallel port 1 serial ports 1 VGA Port 8 USB 2.0 ports (4 rear, 4 optional) 1 line in, line out, microphone in 1 RJ45 connector
Chassis	Micro Tower ATX
Keyboard	Wearnes Keyboard
Mouse	Wearnes Mouse
Monitor	Wearnes 15" SVGA Digital Monitor Wearnes 17" SVGA Digital Monitor (optional) Wearnes 15.1" TFT-LCD Monitor (optional)
Speaker	Wearnes Active Speaker (optional) Wearnes Active Speaker with Subwoofer (optional)
Power Supply	250 Watt
Operating System Supported	Windows® 2000 Professional Windows® XP Home/Professional Edition
Limited Warranty Period	Three year service & one spare part

7071