



Amadeus 7900L

Specifications

Processor	Supports Socket 775 for Intel® P4 3xx/ 5xx/ 6xx/ Pentium D (805/820/920/925/930), Celeron D, Core 2 Duo processors Supports FSB 1066/800/533MHz EIST Technology Supports Hyper-Threading (HT) Technology
Chipset	VIA® P4M900
System Memory	Supports two DDRII memory modules, up to 4GB Supports DDRII 667/533/400 memory interface
Video	Integrated S3G UniChrome™ Pro IGP Graphics, Share Memory up to 256MB
Audio	Integrated 8 channel HD audio codec Realtek ALC888
On-Board IDE	Supports 1 Ultra ATA-133 port Supports 2 Serial ATA-150 ports
Standard Diskette Size	3.25"/1.44MB FDD
Optical Drive	Optional
Network Interface	Integrated Realtek® RTL8201CL 10/100 LAN
Modem	56kbps V.92 Internal PCI Fax/Modem (optional)
Expansion Slots	One PCI Express x16 slot Two PCI 2.3 32-bit PCI bus slots
Drive Bays	Two 5.25" for CD-ROM Drive One 3.5" for FDD Two 3.5" (hidden) for HDD
I/O Interface	1 PS/2 keyboard & mouse 1 parallel port 1 serial ports, COM1 on Rear IO 8 USB 2.0 ports (4 rear, 4 optional) 6 flexible audio jacks 1 RJ45 connector
Chassis	Micro Tower ATX
Keyboard	Wearnes Keyboard
Mouse	Wearnes Mouse
Monitor	Wearnes 15" SVGA Digital Monitor Wearnes 17" SVGA Digital Monitor (optional) Wearnes 15.1" TFT-LCD Monitor (optional)
Speaker	Wearnes Active Speaker (optional) Wearnes Active Speaker with Subwoofer (optional)
Power Supply	300 Watt

7387