



## Df Ya JYf Y 79( 5L&

### Specifications

<b>Processor</b>	Supports Socket 775 for Intel® P4 3xx/ 5xx/ 6xx/ Pentium D (805/820/920/925/930), Celeron D, Core 2 Duo processors Supports FSB 1333/1066/800/533MHz EIST Technology Supports Hyper-Threading (HT) Technology
<b>Chipset</b>	Intel® 945GC
<b>System Memory</b>	Supports two DDRII memory modules, up to 4GB Supports DDRII 667/533/400 memory interface
<b>Video</b>	Integrated Intel® GMA950 Graphics, DVMT up to 224MB
<b>Audio</b>	Integrated 6 channel HD audio codec Realtek® ALC888
<b>On-Board IDE</b>	Supports 1 Ultra ATA-133 port Supports 4 Serial ATA-150 ports
<b>Standard Diskette Size</b>	3.25"/1.44MB FDD
<b>Optical Drive</b>	Optional
<b>Network Interface</b>	Integrated Realtek® RTL8101E 10/100 LAN
<b>Modem</b>	56kbps V.92 Internal PCI Fax/Modem (optional)
<b>Expansion Slots</b>	One PCI Express x16 slot One PCI Express x1 slot Two PCI 2.3 32-bit PCI bus slots
<b>Drive Bays</b>	Two 5.25" for CD-ROM Drive One 3.5" for FDD Two 3.5" (hidden) for HDD
<b>I/O Interface</b>	1 PS/2 keyboard & mouse 1 parallel port 2 serial ports, COM1 on Rear IO, COM2 via pin header 8 USB 2.0 ports (4 rear, 2 front, 2 optional) 3 flexible audio jacks 1 RJ45 connector
<b>Chassis</b>	Micro Tower ATX
<b>Keyboard</b>	Wearnes Keyboard
<b>Mouse</b>	Wearnes Mouse
<b>Monitor</b>	Wearnes 15" SVGA Digital Monitor Wearnes 17" SVGA Digital Monitor (optional) Wearnes 15.1" TFT-LCD Monitor (optional)
<b>Speaker</b>	Wearnes Active Speaker (optional) Wearnes Active Speaker with Subwoofer (optional)
<b>Power Supply</b>	300 Watt

\*\*\*7507\*\*\*