



Quadra VX-7

Specifications

Support Processor	VIA® C7-M 772 @ 1.2 GHz ULV Processor, 5W
L2 Cache	128 KB
FSB	400 MHz
Chipset	VIA® VX700
Graphics & Video Module	Integrated VIA® VX700 Shared Video Memory
Main Memory	One Slot SO-DIMM DDRII 1GB 533MHz , max 1GB
Display	7" TFT Super Glare Type WVGA (800 x 480 px) Touch Screen + Stylus Pen
PC Cards Slot	-
Card Reader	MMC/SD/MS/MS PRO 4-in-1 Card Reader
Hard Disk Drive	Support 1.8" 8mm IDE HDD 60 GB, up to 160 GB
Optical Drive	External Combo Drive via USB
Bluetooth	Built-in Bluetooth
WebCam	0.3 MP WebCam
LAN / Modem	Built-in Ethernet LAN 10/100 Module Built-in 802.11b/g WLAN card
I/O ports	Monitor (VGA) Port X 1 (DVI) High Speed USB2.0 Port X 2 Microphone input X 1 Line Out / Headphone Output X 1 RJ-45 10/100 LAN Port X 1
Audio	HD Audio Compliant, Built-in 2 x High Quality Speakers (1.5W)
Battery Type	4 cells (Li-ion) 2200mA, approx. 3.5 hrs
AC Adapter	19V DC, 50W / Input: 100 ~ 240V AC, 50/60Hz universal
Dimension	230(L) X 171(D) X 29.4(H) mm
Weight	Approx. 0.97 KG include battery

VX7